



MS842

Combine the best

The Unitech MS842 combines efficiency, durability and reliability into a compact, lightweight handheld scanner. Supporting all common 1D and 2D barcodes, the MS842 provides several solutions to help medical professionals, hospitals, and pharmacies manage and control their inventory. Even the smallest high-density barcodes on medicine packaging are fully supported with the Unitech MS842 HD option!

Efficiency at the highest level

With the seamless integration of its high-performance decoder and scan engine, the MS842 provides one of the most efficient scanning solutions in its class. It can be easily used in high demanding healthcare and pharmaceutical applications like blood bag scanning, inventory management, etc. With an extended depth of field, wide scan angle and aggressive scan rate, the MS842 provides performance and reliability wherever it is used.

Durability & low cost of ownership

Accidents happen in every business setting, and the MS842 is ruggedly designed to perform under adverse conditions. With its durable construction, the MS842 can even withstand a 1.8 meter drop to concrete. So, if a worker happens to drop their scanner, they can pick it up and continue scanning without

interruption. No downtime, no replacement, and no service needed. The MS842 also features an IP42-rated environmental seal against moisture and dust, and a long life trigger design that guarantees 10 million scans.

Practical and compact

Certain applications, such as medical inventory management, consist of very scan-intensive circumstances. With the weight of just 210 grams, the MS842 is very user friendly and ideal for those tasks that require high volume scanning. The ergonomic and compact design reduces fatigue and ensures user comfort during periods of intensive scanning operations. With two operational modes, trigger mode and presentation mode, the MS842 simply allows users the freedom to do more.

Main Features

- High performance engine & decoder
- Supports all 1D and 2D barcodes
- Long life trigger design
- Durable rugged scanner: IP42 and 1.8 drop spec.
- Lightweight: only 210 grams
- High reading distance

unitech
because we care

Operational & Performance

Technology	Image sensor, 752 x 480 px
Light source	Illumination: 625nm LED Aiming: 655nm VLD
Max. resolution	SR: 5mil (code 39) - 6,7mil (PDF417) HD: 3mil (code 39) - 4mil (PDF417)
Scan rate	100 scans/sec
Reading angle	Skew: 60° Pitch: 60°
Reading distance	(DOF PCS80%)

SR	near	far
Code 39, 5mil	5.3cm	19.1cm
PDF417, 6.7mil	8.6cm	18.0cm

HD	near	far
Code 39, 3mil	4.1cm	9.7cm
PDF417, 4mil	4.6cm	8.9cm

* = dependents on width of barcode

Symbologies

Decode Capability	<p>1D: Code 39, Full ASCII Code39, Interleave 2 of 5, Standard 2 of 5, UPC A/E, Delta Code, Label Code, MSI/ Plessey, Codabar, Code 11, EAN8/13, Code 93, Code 128, EAN128, Code32, Toshiba Code, GS1 databar Code.</p> <p>2D: PDF417, MicroPDF417, Datamatrix, QR Code, Micro QR Code, Aztec, RSS, Composite, TLC -39, MaxiCode.</p> <p>Postal: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX).</p>
-------------------	---

Power Source

Operation voltage	DC 3V to 5V
Consumption	Operation mode: <400mA Standby mode: <160mA

Data Formatting

Prefix, Suffix, Code ID, Reformatting Date

Operation mode

Trigger mode, Presentation mode

Connectivity

USB, RS232

Enclosure

Scanner dimension	176mm x 74 mm x 89mm
Scanner weight	210g (without cable)
Switch life	10 million time

Environmental

Operating temperature	0°C to 50°C
Storage temperature	-30°C to 70°C
Relative humidity	95% non-condensing
Drop test to concrete	1.8 meter (scanner only)
IP rate	IP42
ESD protection	Functional after 8K contact and 12K air

Accessories

Hands Free Stand
Interface cable

Warranty

1 year

Regulatory approvals

CE, FCC, BSMI, VCCI

Unitech Europe

Tilburg, The Netherlands
 • Tel.: +31 (0)13 460 9292
 • Email: Info@eu.ute.com
 • Website: <http://eu.ute.com>



unitech
because we care

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan